


LED A-A+ IP54 CE

Codice Code	Finitura Finishing	K	Flusso Flux	CRI	Potenza Wattage	Dimensioni Dimension	Ottica Optics	Peso Weight
10015-GR-LED-S	grigio grey	3000K	1350 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg
OBO002GR	grigio grey	4000K	1430 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg
10015-AN-LED-S	antracite anthracite	3000K	1350 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg
OBO002AN	antracite anthracite	4000K	1430 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg
10015-MA-LED-S	marrone brown	3000K	1350 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg
OBO002MA	marrone brown	4000K	1430 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg



Informazioni sensore Sensor information

Altezza installazione Height of installation
2,53,5 m

Campo di regolazione distanza di rilevamento Sensing distance adjustment range
MIN: 1m
Max: 8m

Campo di regolazione angolo di rilevamento Sensing angle adjustment range
360°

Potenza di trasmissione < 0,2 mW
Transmission power <0,2 mW

SENS TIME LUX

E-A+ IP54 CE

Codice Code	Finitura Finishing	E27	Flusso Flux	CRI	Potenza Wattage	Dimensioni Dimension	Ottica Optics	Peso Weight
10015-GR	grigio grey	E27	—	—	2x75W max - 220V	Ø275x86 mm	—	2,5 Kg
10015-AN	antracite anthracite	E27	—	—	2x75W max - 220V	Ø275x86 mm	—	2,5 Kg
10015-MA	marrone brown	E27	—	—	2x75W max - 220V	Ø275x86 mm	—	2,5 Kg

